



## Pertec Interface Flash Tape

The Pertec Interface Flash Tape allows you to retire your legacy reel-to-reel tape drive and replace it with a compact unit that uses readily available flash cards as the media rather than bulky and hard-to-get tape reels.

The Flash Tape unit is a plug & play replacement for your current Pertec interface tape drive, so you can continue to use the software that you use with your current drive - just get rid of all those heavy and hard to store tapes and replace them with compact flash cards.

The flash tape is can replace all Pertec tape densities - 800, 1600, 3200 or 6250 BPI. Replacing your old drive couldn't be simpler - just unplug the old drive and connected the Pertec cables to the flash drive, plug in the power and you are done!

Not only do you gain the advantage of smaller and more robust media, but you can also have storage capacities that are simply not available with tape.

Flash tape drives are also available with SCSI interface to replace legacy DAT, 8mm, DLT, 3480/3490, 3590 and reel-to-reel drives. Contact your Avax sales representative form more information.

## FEATURES

- A Pertec interface Tape Drive Emulation writing to Compact Flash card
- Zero tape positioning times – useful for quick file positioning when reading the “tape”.
- Removable flash card can be treated as a single tape media
- Solid state Flash disks provide much more rugged media than tape.
- Eliminates problems of slow back-ups shoe-shining the tape drive, which eventually leads to failures.
- Simple Plug & Play installation
- A small, lightweight alternative to a real tape drive.
- No additional software or drivers required. The Flash drive simply replaces your existing Pertec interface drive.
- Works with any operating system that supports a Pertec interface drive
- Use in conjunction with a SCSI interface drive on another operating system as a simple way of transferring data between operating systems.



WITH THIS

## SPECIFICATIONS

### Power:

Universal 97- 270 V Auto sensing

### Dimensions:

A4 Foot print or optional 1U Rack mount enclosure

### Interface:

Standard Formatted Pertec - 2 x 50 way connectors

### Flash Card

PCMCIA Card, SD Card, Microdrive or Compact Flash

### Transfer Rate:

10 Mbytes/sec (burst)

### Shipping weight:

4 Kg (Desktop unit)

### AVAX INTERNATIONAL

PO Box 542

Hillsburgh, Ontario N0B 1Z0 Canada

Tel: (647) 367-1039 or (877) 401-1892

Fax: (647) 438-2242

[www.avax.com](http://www.avax.com)



Available from:

